

touchTymp MI 24

The first full 10.4" touchscreen tympanometer

A new generation of intuitive impedance testing.

Simply intuitive

The touchTymp combines a full 10.4" touchscreen interface and an innovative icon structure for amazingly intuitive handling. The large colour display allows the user to easily change parameters with a maximum of 3 clicks. touchTymp simply improves every professional's daily workflow.

Patient-focused testing

Designed to help the user remain focused on the patient rather than on the measurement - the unique light bar on the ergonomic and responsive probe provides a real-time progression of the test. Plus, advanced light indicators show which ear is tested and the test result.

Comprehensive test protocols

The touchTymp MI 24 provides comprehensive standard protocols for immediate operation of all screening test processes: tympanometry with 226 Hz, tympanometry with automatic acoustic reflexes, or tympanometry with acoustic reflexes at a fixed level. The optional high-frequency probe tone of 1 kHz is ideal for providing reliable results when testing newborns.

Printing made easy

Test results and reports can be printed quickly using the built-in printer. When placing the probe into the probe holder, the test results will print automatically - touchTymp really is that easy and intuitive.

Features at a glance

- Provides test results within seconds
- Allows testing from infants to adults
- Customisable to suit individual needs
- Full touch-based interface for intuitive handling
- Innovative probe lights allow for patient-focused operation
- Probe tone 226 Hz, optional high-frequency probe tone 1 kHz
- Acoustic reflex frequencies 500 Hz, 1 kHz, 2 kHz, 4 kHz (ipsi- and optional contralateral)
- High resolution and quick screen transitions
- Built-in printer



Technical Data touchTymp MI 24

TYMPANOMETRY

Probe Frequency	226 Hz \pm 1 %, 85 dBSPL (69 dBHL) \pm 1.5 dB
Optional High Frequency	1 kHz \pm 1%, 69 dBSPL (69 dBHL) \pm 1.5 dB
Pressure Range	-400 to +200 daPa
Accuracy of Pressure	\pm 5 % or \pm 10 daPa
Volume Range	0.1 to 8.0 ml at 226 Hz
Compliance Range	0.1 to 8.0 ml at 226 Hz
Accuracy of Volume	\pm 5 % or 0.1 ml
Test Time	3 - 5 seconds

REFLEX MODE

Test Frequencies	0.5, 1, 2, 4 kHz \pm 1 %
Test Method	Ipsilateral; optional contralateral
Level Ipsilateral	70 to 105 dBHL
Level Contralateral	70 to 120 dBHL with contra phone receiver
Level Setting	Automatic or fixed
Ipsilateral Reflex Test	With AGC

DEVICE GENERAL

Display	10.4" Graphic LED Display with resistive touchscreen
PC Interface	USB
Probe	Lightweight hand-held probe with built-in control light and switch
Printer	Fast, virtually silent 4-inch thermal printer
Power Supply	Mains 100 to 240 V \sim \pm 10 %, 50 - 60 Hz \pm 10 %
Dimensions	W 30 x D 34.5 x H 14.8 cm
Weight	3.2 kg

STANDARD

IEC 60601-1, class I, type B, IEC 60645-5, type 2, according to medical device directive 93/42/EEC



STANDARD COMPONENTS

Pen Probe, built-in calibration cavity, Sanibel ear tip kit, built-in printer and roll of thermal paper, mains cable, probe floss kit, MAICO USB flash drive kit, Impedance Module software, USB cable, cleaning cloth, touch pen

OPTIONAL ACCESSORIES

Contralateral phones: DD45 C, CIR22, IP30

SANIBEL

We highly recommend to use Sanibel disposables in order to guarantee optimal test results.



Specifications are subject to change without notice.

<div style="background-color: #92d050; color: white; padding: 5px; text-align: center;">Standard Components</div>			
	touchTymp device with printer	Pen Probe	Ear tip kit
<div style="background-color: #808080; color: white; padding: 5px; text-align: center;">Optional Accessories</div>			
	DD45 C	CIR22	IP30



MAICO Diagnostics GmbH

Sickingenstr. 70-71 · 10553 Berlin · Germany
 Tel.: +49 30/70 71 46-50 · Fax: +49 30/70 71 46-99
 sales@maico.biz · www.maico.biz